




DOCUMENTATION SHEET

Anti-vibration Mountings
Type Circular Buffer TXC

TXC
CIRCULAR BUFFER



DIMENSIONS

Type	Dimensions (mm)			Stiffness (N/mm)		Max. load (N)		Stock
	D	H	G	Cz	Cxy	Fz	Fxy	
TXC010010S20A45	10	10	M4	50	59	25	59	
TXC010010S20A60	10	10	M4	100	85	50	85	s
TXC015015S20A45	15	15	M4	60	45	60	67,5	s
TXC015015S20A60	15	15	M4	100	68	100	102	s
TXC015020S20A45	15	20	M4	40	38	60	76	
TXC015020S20A60	15	20	M4	80	59	120	118	
TXC015030S20A45	15	30	M4	23	8	57	28	
TXC015030S20A60	15	30	M4	47	15	117	52,5	
TXC020015S20A45	20	15	M6	125	48	125	72	s
TXC020015S20A60	20	15	M6	250	70	250	105	
TXC020020S20A45	20	20	M6	150	25	180	50	s
TXC020020S20A60	20	20	M6	230	39	276	78	s
TXC020025S20A45	20	25	M6	80	14	120	42	s
TXC020025S20A60	20	25	M6	120	24	180	72	
TXC025020S20A45	25	20	M6	90	47	108	94	
TXC025020S20A60	25	20	M6	230	65	276	130	
TXC025025S20A45	25	25	M6	65	33	97	99	
TXC025025S20A60	25	25	M6	110	53	165	159	s
TXC025030S20A45	25	30	M6	55	26	110	91	
TXC025030S20A60	25	30	M6	80	40	160	140	s
TXC030015S20A45	30	15	M8	400	71	400	107	
TXC030015S20A60	30	15	M8	700	95	700	143	
TXC030020S20A45	30	20	M8	220	59	330	118	
TXC030020S20A60	30	20	M8	425	78	637	156	
TXC030030S20A45	30	30	M8	108	32	216	112	
TXC030030S20A60	30	30	M8	175	53	350	186	s
TXC040030S20A45	40	30	M8	240	54	480	189	
TXC040030S20A60	40	30	M8	530	87	1060	305	s
TXC040040S20A45	40	40	M8	140	31	378	155	s
TXC040040S20A60	40	40	M8	222	49	666	245	s
TXC050030S20A45	50	30	M10	350	79	70	277	
TXC050030S20A60	50	30	M10	680	135	1360	473	
TXC050040S20A45	50	40	M10	167	53	500	265	
TXC050040S20A60	50	40	M10	333	85	1000	425	s
TXC050045S20A45	50	45	M10	128	41	410	226	
TXC050045S20A60	50	45	M10	241	74	770	407	
TXC050050S20A45	50	50	M10	115	23	400	138	s
TXC050050S20A60	50	50	M10	190	41	665	246	s
TXC075040S20A45	75	40	M12	417	151	1250	755	
TXC075040S20A60	75	40	M12	750	213	2250	1065	
TXC075050S20A45	75	50	M12	348	78	1220	468	
TXC075050S20A60	75	50	M12	636	125	2225	750	
TXC075060S20A45	75	60	M12	275	57	1100	456	
TXC075060S20A60	75	60	M12	520	85	2080	680	
TXC100040S20A45	100	40	M16	800	185	2400	925	
TXC100040S20A60	100	40	M16	1700	246	5100	1230	
TXC100075S20A45	100	75	M16	460	71	2300	781	
TXC100075S20A60	100	75	M16	680	126	3400	1386	
TXC100100S20A45	100	100	M16	215	57	2150	1026	
TXC100100S20A60	100	100	M16	525	95	5250	1710	
TXC150075S20A45	150	75	M16	900	158	4500	945	
TXC150075S20A60	150	75	M16	1500	252	7500	1580	
TXC150150S20A45	150	150	M16	600	69	9000	1518	
TXC150150S20A60	150	150	M16	1090	101	16350	2222	
TXC200100S20A45	200	100	M20	914	172	6400	3096	
TXC200100S20A60	200	100	M20	1600	285	11200	5130	

CHARACTERISTICS

